



NOTES:

1. ALL DIMENSIONS IN MM
2. GENERAL TOLERANCE: X.X=±0.4  
X.XX=±0.25
3. TERM. NOS. FOR REFERENCE ONLY.
4. CONTACT RATINGS: 25mA @24VDC. (Switch)  
100mA @50VDC. (Carry)
- ▲ 5. CONTACT MATERIAL:  
CONTACTS: (MOVABLE) Copper w/Gold Plate  
TERMINALS: BRASS w/Gold Plate
6. INSULATION RESISTANCE:  
100 Mega-OHMS min. @500VDC
7. CONTACT RESISTANCE:  
50 MILLI-OHMS typical @2-4VDC @100mA
8. OPERATING TEMP.:-40°C to +80°C
9. PACKAGE: IN DISPENSING TUBES  
WITH ALL POLES IN THE "OFF" POSITION.
- ▲ 10. TOP TAPE SEAL FOR FLUX WASH

**E-SWITCH**®

REV. A		12416		RELEASED FOR PRODUCTION		9/12/02		CJB	
REV. ECN No.		12416		DESCRIPTION		DATE		CHKD	
THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED									
TITLE		KAJ10 1A GT		SCALE		DATE		DR	
REV. A		12416		DESCRIPTION		DATE		CHKD	
REV. ECN No.		12416		DESCRIPTION		DATE		CHKD	
LOW PROFILE W/TAPE SEAL									
SCALE		2:1		DATE		9/12/02		DR	
DR		CJB		DWG		W823330		REV	
REV		A		DATE		9/12/02		CHKD	