

Panel mounting frame set - CUC-V04-F-BU/BU-RJ45 - 1407412

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Panel mounting frame set, Degree of protection: IP65/67, Number of positions: 8, Material: Plastic



Key Commercial Data

Packing unit	1 STK
Custom tariff number	85366990
Country of origin	Romania

Technical data

Mechanical characteristics

Standards/specifications	IEC 61076-3-106
Number of positions	8
Connection profile	RJ45
Locking type	Push Pull
Insertion/withdrawal cycles	≥ 750
Color	black

Ambient conditions

Ambient temperature (operation)	-40 °C ... 70 °C
Ambient temperature (storage/transport)	-40 °C ... 70 °C
Degree of protection	IP65

Material data

Flammability rating according to UL 94	V0
Housing material	Plastic

Electrical characteristics

Panel mounting frame set - CUC-V04-F-BU/BU-RJ45 - 1407412

Technical data

Electrical characteristics


Number of positions	8
---------------------	---

Standards and Regulations

Standards/regulations	IEC 61076-3-106
Flammability rating according to UL 94	V0

Drawings

Dimensional drawing



Panel mounting frame dimensional drawing

Classifications

eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27261207
eCl@ss 7.0	27440210
eCl@ss 8.0	27440210
eCl@ss 9.0	27440210

ETIM

ETIM 3.0	EC002310
ETIM 4.0	EC002310
ETIM 5.0	EC002310

UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501

Panel mounting frame set - CUC-V04-F-BU/BU-RJ45 - 1407412

Classifications

UNSPSC

UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC B.01742

Accessories

Accessories

Data plug

RJ45 connector - CUC-V04-RJ45-POBK-8 - 1407413



RJ45 connector, IP65/IP67, with push/pull interlocking (version 4), plastic housing, for 10 Gbps, for 24 ... 28 AWG stranded conductors